



| | |
|-----------------------------|--|
| Gauge | 16 A60 only |
| Hinge Reinforcements | 7 gauge |
| Closer Reinforcement | Standard |
| Flush metal top cap | Standard or seamless |
| Thickness | 1 3/4" only |
| Width | 4'-0" (48") max per leaves |
| Height | 8'-0" (96") max |
| Edge Seam | Visible (standard) or seamless |
| Core | Pyrophobic proprietary core design only |
| Details | Core permanently bonded to door skins by high strength pressure sensitive adhesive |

| Fire Rating | | | | |
|--------------------|------------------|-------------------|------------------|-------------------|
| Door Type | Max Width | Max Height | Thickness | Max Rating |
| Single Swing | 4'-0" (48") | 8'-0" (96") | 1 3/4" | 180 min. |
| Standard Pair* | 8'-0" (96") | 8'-0" (96") | 1 3/4" | 180 min. |
| Double Egress** | 8'-0" (96") | 8'-0" (96") | 1 3/4" | 90 min. |

* Astragals are required on all pairs
 ** Astragal and fire exit hardware required on all double egress pairs

**Evaluated to UBC 7-2 (1997),
 UL 10C (1998) and NFPA 252**

**Vision lites of 100 square inches are
 approved up to 90 minutes**



Concept Frames
 2015 Industrial Drive, Newton, NC 28658
 PH: 888-234-9455 Fax: 800-631-9089
www.ConceptFrames.Com

Date: 1-3-2012

Temperature Rise Doors