

# Door Quote/Order Form

Customer Support: (888) 234-9455

ATTENTION: Form must be downloaded and saved to your files before you fill out and submit.

Rev. 06-20-24

Customer: \_\_\_\_\_

Contact Person: \_\_\_\_\_

PO#: \_\_\_\_\_

Job Name: \_\_\_\_\_

Today's Date: \_\_\_\_\_

Due Date: \_\_\_\_\_

Sales: \_\_\_\_\_

Page: \_\_\_\_\_ of \_\_\_\_\_

☐

Quote

☐

Order

Quoted: \_\_\_\_\_

Ship to:

☐

Customer

☐

Jobsite

☐

CPU

Line	Quantity	Handing	Gauge	Material	Opening Width (in)	Opening Height (in)	Net Width (in)	Net Height (in)	Undercut	Thickness	Fire Label (Min.)	Door Style	Core	Seam @ Edge	Bevel Edge	Locations	Hinges (std BS 1/4")	Lock/Strike/ Backset	Astragal Flat or Z	Closer	Mark #	Notes
1																						
2																						
3																						
4																						
5																						
6																						
7																						
8																						

## Legend

<div>Material</div> <div><div>Gauge</div><div>8 - 18 ga.</div><div>6 - 16 ga.</div><div>4 - 14 ga.</div><div>2 - 12 ga.</div></div> <div><div>Material</div><div>A = A60</div><div>S = SS</div></div>	<div>Door Style</div> <div><div><div></div><div>F</div></div><div><div></div><div>VL</div></div><div><div></div><div>NL</div></div><div><div></div><div>HG</div></div><div><div></div><div>FG</div></div><div><div></div><div>LV</div></div><div><div></div><div>2E</div></div><div><div></div><div>6E</div></div></div>	<div>Core</div> <div>P - Polystyrene</div> <div>S - Steel Stiffened</div> <div>T - Temp Rise*</div> <div>*List Degree</div>	<div>Locations</div> <div>AM - Amweld</div> <div>CE - Ceco</div> <div>CU - Curries</div> <div>ME - Mesker</div> <div>NR - New Republic</div> <div>OR - Old Republic</div> <div>PI - Pioneer</div> <div>PR - Premier</div> <div>ST - Steelcraft</div> <div>*Provide Seperate Drawing</div>
<div>Thickness</div> <div>4 - 1-3/4"</div> <div>8 - 1-3/8"</div> <div>O - Other (list)</div>	<div>Lock/Strike</div> <div><div>1 - 161</div><div>2 - 161x2 1/8" DL</div><div>3 - 160</div><div>4 - 86 Edge</div><div>5 - Mortise*</div><div>6 - 1-1/2" DL</div></div> <div><div>A - ASA</div><div>D - DL Strike</div><div>F - Flushbolt</div><div>N - None</div><div>T - T Strike</div><div>AD - ASA x DL</div><div>AF - ASA x FB</div></div> <div><div>B - Surf. Bolts</div><div>C - Conc. Vert. Rod</div><div>M - Mort. Panic</div><div>P - Push/Pull</div><div>R - Rim Panic</div><div>S - Surf. Vert. Rod</div></div>	<div>Seam and Edge</div> <div>N - Not Seamless</div> <div>B - Bondo Seamless</div> <div>W - Welded Seamless*</div> <div>*N/A on Hemmed Edge</div>	<div>Astragals</div> <div>FL - Flat Loose</div> <div>FI - Flat Inst.</div> <div>ZL - Z Loose</div> <div>ZI - Z Inst.</div> <div>N - None</div>

## Notes:

