



Gauge	16 A60 only
Hinge Reinforcements	7 gauge
Closer Reinforcement	Standard
Flush metal top cap	Standard or seamless
Thickness	1 3/4" only
Width	4'-0" (48") max per leaves
Height	8'-0" (96") max
Edge Seam	Visible (standard) or seamless
Core	Pyrophobic proprietary core design only
Details	Core permanently bonded to door skins by high strength pressure sensitive adhesive

Fire Rating				
Door Type	Max Width	Max Height	Thickness	Max Rating
Single Swing	4'-0" (48")	8'-0" (96")	1 3/4"	180 min.
Standard Pair*	8'-0" (96")	8'-0" (96")	1 3/4"	180 min.
Double Egress**	8'-0" (96")	8'-0" (96")	1 3/4"	90 min.

* Astragals are required on all pairs
 ** Astragal and fire exit hardware required on all double egress pairs

**Evaluated to UBC 7-2 (1997),
 UL 10C (1998) and NFPA 252**

**Vision lites of 100 square inches are
 approved up to 90 minutes**



Concept Frames, Inc.
 2015 Industrial Drive, Newton, NC 28658
 PH: 888-234-9455 Fax: 800-631-9089
www.ConceptFrames.Com

Date: 1-3-2012

Temperature Rise Doors